



CARRATHOOL SHIRE COUNCIL

"Promoting our future through diversity"

PLANT FOR SALE / TRADE-IN

Plant No. 2578 – Tri Star Tri-Axle Side Tipper Trailer

TO SUPPLY COUNCIL WITH SIMILAR TYPE TRAILER (GST INCLUSIVE)

QUOTATIONS MUST INCLUDE:

- Trailer to be a side tipper
- King pin to be 50mm
- Landing legs to be dual speed type and capable of safely carrying a full loaded trailer
- Quoter nominated make and model
- All tyres to be 11.00 – 22.5 tubeless radials. One spare tyre and rim assembly for the same specification as the others. Two spare carriers mounted in a vertical position under the floor of the trailer
- An Aeroquip type P/N FB 5601-16 coupling for the hydraulic hoist is to be mid mounted at the most forward point of the trailer. All coupling and sockets to be located and shielded from possible hoist oil leakage. Couplings and sockets must not be recessed into the body of the trailer
- All electrical wiring must be protected with an insulated conduit over and above the natural outcase of the wire. An additional conduit must be securely attached to the body of the trailer. The electrical entry socket is to be Utilux type P/N H1715BK mounted adjacent to the other couplings. The gates are to be air operated. All lamps must be protected to avoid damage when tipping
- Brake airline couplings to be Ryco type P/N 320 and 303 and again mounted with the other sockets
- Body floor to be at least 5mm thick Bisalloy 360 steel. Body must be at least 18 cubic metres capacity. Sides to be approximately 1 (one) metre in height and length to be approximately 9 (nine) metres long. Rear 1500mm of sides to be 5mm Bisalloy 360 and tailgate to be 5mm Bisalloy 360. Remainder of sides and front to be Bisalloy 80
- All welds must be run longitudinally on frame members. Special care must be taken to avoid weak spots at the finish of all welds
- One copy of parts book must be supplied for all components of the trailer – CD preferred
- Ring feeder to be attached to rear of trailer
- Air bag suspension
- Reversing alarm to be fitted to rear of trailer (variable pitch) RMS compliant
- Mud guards to be attached to the side of trailer over front and rear wheel assemblies with mud flaps at rear
- Axles to be fitted with disc brakes. Boosters and brake calliper components to be protected from stone damage where possible
- Number of weeks (after official order) for delivery to be nominated.
- Trailers to be delivered to Council's Goolgowi Works Depot. Acceptance of delivery will be refused if trailer does not comply with specifications.
- Enviro Tarp System (Electric)



*** Please note that Council will retain all two-way radios ***

Inspections may be arranged by contacting Council's Office during normal business hours on (02) 6965 1900.

All quotations must be completed on an Official Council Quotation Form and placed in a sealed envelope clearly marked **'Confidential Vehicle Quotation'** and clearly state the quotation name and plant number. This form can be obtained from Council. Quotations are to be received at the Administration Centre Goolgowi or by email at tenders@carrathool.nsw.gov.au by 12 noon Wednesday 31st July 2024.

All persons are advised that it is their responsibility to ensure that their quotation is received prior to the advertised closing date and time.

- Faxed quotations will **not** be considered.
- The highest / lowest or any quotation will not necessarily be accepted.

Council Contact: Bert Breuling – Manager Fleet & Town Services (02) 6965 1900 or 0429 651 348.

RICK WARREN
GENERAL MANAGER

PO Box 12
GOOLGOWI NSW 2652
Ph: 02 6965 1900
Email: council@carrathool.nsw.gov.au